

SPRING-ACTUATED, RETRACTABLE-BLADED SURGICAL SCALPEL

Inventors: Mark L. Iske
7821 Villanueva Street
Albuquerque, New Mexico 87109

Timothy C. Thompson
40 Chaco
Los Alamos, New Mexico 87544

and

Charles T. Gregg
1060 Los Pueblos Road
Los Alamos, New Mexico 87544

CITIZENS OF THE UNITED STATES

EXPRESS MAIL CERTIFICATE NO.: EV 300139365 US

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is based upon and claims the benefit of United States Provisional Patent Application Serial Number 60/405,442 by Mark L. Iske, et al. entitled "Spring-Actuated, Retractable-Bladed Surgical Scalpel" filed August 23, 2002, the entire contents of which is hereby specifically incorporated by reference for all it discloses and teaches.

FIELD OF THE INVENTION

The present invention relates generally to surgical cutting instruments and, more particularly, to surgical scalpels having spring-actuated retractable blades.

BACKGROUND OF THE INVENTION

It is well known that existing surgical cutting implements provide a significant potential for harm to surgeons and support personnel. That is, with attention directed toward the patient, rapid handling of surgical instruments having exposed sharp edges occasionally leads to cuts and puncture wounds with loss of integrity of surgical gloves, thereby increasing the risk of life-threatening infectious diseases.

In U.S. Patent No. 5,403,337 for "Retractable-Bladed Surgical Scalpel" which issued to David Platts on April 04, 1995, a spring-actuated retractable-bladed scalpel having interchangeable blades is described. Shipping and use of this instrument has identified three difficulties. First, if the package containing the scalpel is dropped, there is a likelihood that the cutting edge will pierce the sterile package within which it is located. Moreover, only a limited number of scalpel blades can be used with the single-size slide member, and the slide moves with difficulty within the channel in the handle if the size of the scalpel is increased to accommodate additional blade sizes.

The Saf-T-Pass Retractable Scalpel, a recently marketed product from Surgical Specialties Corporation, minimizes the risk of scalpel injury by providing a surgical scalpel having a blade which is deployed when a locking button disposed on the scalpel's slide and moving therewith is pushed forward relative

to the scalpel's handle by a user of the scalpel. A final action of rotating the locking button secures the slide which holds the blade in the open position. The blade is retracted when the locking button is rotated in the reverse direction by the user and the slide is permitted to move under the action of a spring thereon, thereby shielding the blade within the handle in which it originally was situated. A movable slide cover prevents the slide from being moved forward until the slide cover is drawn rearward by the user, rendering the deployment of the surgical blade a two-step process.

Accordingly, it is an object of the present invention to provide a retractable-bladed surgical scalpel where accidental piercing of the sterilized packaging is prevented when packaged scalpels are dropped or otherwise roughly handled.

Another object of the present invention is to provide a retractable-bladed surgical scalpel which can accept a plurality of popular scalpel blades.

Still another object of the invention is to provide a retractable-bladed surgical scalpel having smooth motion for deployment and retraction of the cutting blade.

Yet another object of the invention is to provide a retractable-bladed surgical scalpel for which the cutting blade may be deployed by a single motion by the user.

Additional objects, advantages and novel features of the invention will be set forth in part in the description which follows, and in part will become apparent to those skilled in the art upon examination of the following or may be learned by practice of the invention. The objects and advantages of the invention may be realized and attained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

SUMMARY OF THE INVENTION

To achieve the foregoing and other objects, and in accordance with the purposes of the present invention, as embodied and broadly described herein the surgical scalpel having a spring-actuated retractable blade hereof includes: an

elongated handle having a first side and a second side, a first elongated cavity within the handle extending over the long dimension thereof and opening to the outside at both a forward end and a rearward end, the first side having an elongated window therethrough along the long dimension of the handle and located toward the forward end thereof and a second window therethrough disposed toward the rearward end of the handle, the first side further having a first tab extending into the first cavity and located in the vicinity of the edge of the elongated window closest to the rearward end of the handle and a second tab extending into the first cavity between the second window and the rearward end of the handle; the second side having an interior elongated slot therein which terminates before reaching the forward end of the handle and which opens to the outside of the handle at the rearward end thereof; a cutting blade; an elongated slide having a first end and a second end adapted to slidably move longitudinally through the first cavity in the handle and to receive the cutting blade in the region of the first end thereof; a portion adapted to be engaged by and actuated by a digit through the elongated window; a raised, deformable latch in the region of the second end on the side thereof of the digit-engaging portion for engaging either of the first or second tabs in the handle; and a tab adapted to move within the slot in the second side of the handle; means for engaging and reversibly immobilizing the slide when the slide is located in its rearwardmost position in the handle; and means for providing a force on the slide directed toward the rearward end of the handle.

Benefits and advantages of the present retractable-bladed scalpel include a scalpel which can readily accept a plurality of popular scalpel blades and which maintains smooth motion in the deployment of the cutting blade independent of the size of the blade, where the cutting blade may be deployed by a single motion of the movable slide by the user, and where accidental piercing of the sterilized packaging containing the scalpel is avoided when the packaging is dropped or otherwise roughly handled.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and form a part of the specification, illustrate the embodiments of the present invention and, together with the description, serve to explain the principles of the invention. In the drawings:

FIGURE 1 is a projection view of the parts of the scalpel of the present invention showing the two sides of the handle, the two parts of the slide, a coil spring, and a blade.

FIGURE 2 is a projection view of the other side of the scalpel of the present invention shown in FIG. 1 hereof showing the two sides of the handle, the two parts of the slide, a coil spring, and a blade.

FIGURES 3a-3e show cross sectional views of the scalpel of the present invention in its retracted configuration.

FIGURES 4a-4d show cross sectional views of the scalpel of the present invention in its deployed configuration.

DETAILED DESCRIPTION

Briefly, the present invention includes a surgical scalpel having a retractable blade which may be locked in the operating or deployed configuration using a single digit on one hand. Improvements over existing retractable-bladed surgical scalpels include a device for reducing the likelihood that a packaged and sterilized blade can pierce the sterilization envelope as a result of rough handling of the package, a handle which is capable of receiving several sizes of slides bearing cutting blades, and a handle in which the slide contact with the handle is minimized, thereby providing smoother operation of the surgical scalpel.

Reference will now be made in detail to the present preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings. Identical or similar structure is identified by the same callouts. Turning now to FIGURE 1, an exploded projection view of the pieces of the present retractable-bladed scalpel is shown illustrating, in particular, the two sides, **10a** and **10b**, which comprise handle, **12**, the two slide halves, **14a** and

14b which comprise slide, **16**, means for imparting a rearward restoring force to slide **16**, such as a coil spring or a resilient deformable material capable of performing this function, **18**, and cutting blade, **20**. Sides **10a** and **10b**, when brought together, form a cavity in which slide **16** is slidably disposed. Three windows are also illustrated in side **10a** of handle **12**: elongated window, **22**, and small windows, **24a** and **24b**. Tab, **26**, for engaging slide **16** at the location of the termination, **28**, of raised portion, **30**, in the forward end, **32**, thereof when slide **16** is in its deployed position.

FIGURE 1 also illustrates channel, **34**, having stop **36** in the forward end, **38**, thereof in side **10b** of handle **12** in which coil spring **18** is disposed, tab, **40**, disposed on side **14b** of slide **16** for engaging coil spring **18** and tab, **42**, formed on lower flange, **43**, of side **10b** of handle **12** for securing slide **16** in its retracted position. Digit-engaging portion, **44**, of slide half **14a** of slide **16** and deformable latch **46** thereon are also illustrated and will be elaborated upon hereinbelow.

FIGURE 2 shows an exploded projection view of the retractable-bladed scalpel shown in FIG. 1 hereof from the other side thereof. Of note in the inside, **48**, of side **10a** of handle **12**, three tabs or projections are illustrated, **50a**, **50b**, and **50c**, the purpose of which will be explained in detail hereinbelow. Tab **40** and the top edge, **52**, of slide half **14b** form slot, **54**, which is adapted to slidably engage the lower defining portion, **56**, (FIG. 1) of channel **34** on the inside, **58**, of side **10b**. Raised portion, **60**, (FIG. 1) and flange, **62**, of side **10a** of handle **12** cooperate to form a channel which slidably engages tabs, **64a** and **64b**, of lower portion, **66**, of slide half **14b** of slide **16**.

Depressions, **68a**, in slide half **14b** shown in FIG. 1 are adapted to receive posts, **68b**, in slide half **14a** shown in FIG. 2 for joining the two slide halves together.

Matching raised portion, **69a**, and depression, **69b**, capture cutout, **69c**, in blade **20** when the two slide halves are joined, thereby affixing blade **20** to slide **16**. It should be mentioned that blade **20** may be removed from slide **16** for replacement. Further, notch, **70**, in end piece, **72**, of slide half **14b** of slide **16** is adapted to slidably engage flange, **74**, in side **10a** of handle **12**, thereby guiding tab **40** which is also formed in end piece **72**, in channel **34**. A portion, **76**, of the

outside, **78**, of side **10a** is cut away to permit easier access to digit-engaging portion **44** through window **22**.

FIGURE 3a shows a schematic representation of the side view of the assembled scalpel of the present invention with the surgical blade in its retracted position, while FIG. 3b shows the top view thereof. Elongated window **22** and smaller windows **24a** and **24b** are shown in handle **12**. FIGURE 3c shows a schematic representation of the same view as shown in FIG. 3b, except that the top of handle **12** is removed and slide **16** is visible. FIGURE 3d is a schematic representation of the same view as that shown in FIG. 3a except that side **10a** has been removed to expose slide **16**. In particular, digit-engaging portion **44** is clearly visible on slide **16** as is spring **18** and blade **20**.

FIGURE 3e shows a schematic representation of the rear view of the present scalpel showing, in particular, the channel, **80**, formed the cooperation of raised portion, **60**, (FIG. 1) with flange, **62**, of side **10a** of handle **12** which slidably engages tabs, **64a** and **64b**, of lower portion, **66**, of slide half **14b** of slide **16** (all shown in FIG. 2), and cavity, **82**, which is formed by sides **10a** and **10b** of handle **12**.

FIGURES 4a-4d show the same views as FIGURES 3a-3d, respectively, except that the knife is in its extended or deployed condition. Of note is that FIG. 4c illustrates the latching action of deformable latch **46** in slide half **14a** in contact with tab **50a** which secures stop **28** of slide **16** against tab **26** in handle **12** when slide **16** is in its fully forward position. Although handle **12** and slide **16** are fabricated as handle halves **10a** and **10b** and slide halves **14a** and **14b**, respectively, the halves are glued or welded together by any of several well-known joining processes as part of the assembly process for the knife.

The retractable knife of the present invention is packaged for shipment with slide **16** is in its rearward or undeployed position, whereby tab **42** wedges slide **16** firmly within handle cavity **82** (FIG. 3e). This prevents slide **16** from readily moving forward such that blade **20** can puncture a sterilization envelope if the knife is accidentally dropped. In actual operation, latch **46** is may engage any of tabs **50a**, **50b** or **50c**, while being deformable such that slide **16** can slide

through handle cavity **82** under the action of either coil spring **18** or a digit, generally a thumb, in contact with digit-engaging portion **44**. Spring **18** forces latch **46** against whichever of the tabs the latch member is located in forward of it when no external force is applied to digit-engaging portion **44** of slide **16**.

5 As stated hereinabove, handle **12** is relieved **76** in the region of window **22** to provide better access to digit-engaging portion **44** and latch **46**. The shape of relieved portion **76** is chosen such that an operator may readily engage digit-engaging portion **44** of slide **16** in order to deploy blade **20**, while making it more difficult to depress latch **46** until it is desired to retract the blade. Therefore, latch
10 **46** cannot easily be accidentally released by the operator during use of the instrument. Additionally, latch **46** may slightly extend through the rear portion of window **22** when slide **16** is fully deployed to more positively secure slide **16** in its forwardmost position, without affecting the scalpel's resistance to accidental retraction of slide **16**.

15 FIGURE 3c illustrates latch **44** engaging tab **50b** under the action of spring **18** such that the knife is in its closed or retracted position. Given the length of slide **16**, this position would be attained by a user first overcoming the wedging action of tab **42** and moving slide **16** sufficiently far forward using digit-engaging portion **44** of slide **16** such that latch **46** is moved forward of tab **50b**
20 and allowed to be returned thereto under the action of spring **18**. Depressing deformable latch **46** by inserting a solid object through window **24a** will allow slide **16** to move rearward and engage tab **50c**, again under the action of spring **18**. By depressing latch **46** once more, but through window **24b**, slide **16** will move rearward and out of cavity **82** under the action of spring **18**, at which time
25 slide **16** can be removed from handle **12** in order to exchange slides. Tab **50c** and window **24b** together permit longer slides accommodating blades **20** having different sizes and shapes to be used.

As described hereinabove, FIG. 4c illustrates the latching action of deformable latch **46** in slide half **14a** in contact with tab **50a** which secures stop
30 **28** of slide **16** against tab **26** in handle **12** when slide **16** is in its fully forward position.

To improve the slidability of slide **16** within handle cavity **82**, slide **16** is kept from contacting inner walls **48** and **58** of handle **12** when the slide is moved by an operator of the scalpel. Tab **40** and the top edge, **52**, of slide half **14b** form slot, **54**, which is adapted to slidably engage the lower defining portion, **56**, (FIG. 1) of channel **34** on the inside, **58**, of side **10b**. Further, notch, **70**, in end piece, **72**, of slide half **14b** of slide **16** is adapted to slidably engage flange, **74**, in side **10a** of handle **12**, thereby guiding tab **40** which is also formed in end piece **72**, in channel **34**. The upper portion of slide **16** is thereby guided along the inside of handle **12**. Additionally, raised portion, **60**, (FIG. 1) and flange, **62**, of side **10a** of handle **12** cooperate to form channel **80** (FIG. 3e) which slidably engages tabs, **64a** and **64b**, of lower portion, **66**, of slide half **14b** of slide **16**, thereby guiding the lower portion of slide **16** along the inside of handle **12**.

Tolerances and materials are selected such that the scalpel is stable in its operating or deployed mode yet is easily retracted. For surgical or other medical uses, materials must conform to Food and Drug Administration standards. For example, scalpels must be ethylene oxide or gamma-ray sterilizable, or autoclavable. It is anticipated that the slide and handle portions of the present scalpel will chosen for their moldability and for their relative coefficients of expansion and friction such that accurate tolerances can be maintained for operating stability, while maintaining ready relative motion and freedom from binding.

The foregoing description of the invention has been presented for purposes of illustration and description and is not intended to be exhaustive or to limit the invention to the precise form disclosed, and obviously many modifications and variations are possible in light of the above teaching. For example, it would be apparent to one having ordinary skill in the surgical arts after carefully studying the present disclosure that the retractable knife of the present may be fabricated to accommodate either right- or left-handed operators. The embodiments were chosen and described in order to best explain the principles of the invention and its practical application to thereby enable others skilled in the art to best utilize the invention in various embodiments and with

various modifications as are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the claims appended hereto.